

# Claims

- [c1] 1. A grille shelter comprising:  
a housing comprising a rear wall, a first side wall and a second side wall;  
a roof member pivotally connected to a top edge of said housing;  
at least one pivoting panel connected to at least one of said side walls; and  
wherein said at least one pivoting panel is moveable between a first (open) position and a second (closed) position.
- [c2] 2. The grille shelter of claim 1, wherein said roof member is moveable between a first position and a second position.
- [c3] 3. The grille shelter of claim 1, further comprising a platform configured to attach to the housing whereby the grille shelter is secured from toppling in adverse weather or during use.
- [c4] 4. The grille shelter of claim 1, wherein said roof member is further connected to said housing by at least one support member that may include a typical hydraulic or

pneumatic cylinder member that may be connected to at least one of said first and second side walls.

[c5] 5. The grille shelter of claim 2, wherein said roof member is held in said first position by at least one support member.

[c6] 6. The grille shelter of claim 1, further comprising at least one accessory consisting of at least one of the following: hooks, lamps, and shelves.

[c7] 7. The grille shelter of claim 1, further comprising a handle attached to said roof member.

[c8] 8. The grille shelter of claim 7, further comprising a pull cord connected to said handle.

[c9] 9. The grille shelter of claim 1, further comprising a pull cord connected to said roof member.

[c10] 10. The grille shelter of claim 1, wherein said pivoting panels comprises a first section and a second section substantially perpendicular to said first section.

[c11] 11. The grille shelter of claim 10, wherein said first section and said second section are pivotally connected.

[c12] 12. A grille shelter comprising:  
a rear wall;

a first and second side walls connected to opposing ends of said rear wall;  
a roof member pivotally connected to a top edge of said rear wall;  
at least one pivoting panel connected to at least one of said side walls; and  
wherein said at least one pivoting panel is moveable between a first position and a second position and said roof member is moveable between a first position and a second position.

- [c13] 13. The grille shelter of claim 12, wherein a user may use the grille to cook when said roof member and said front wall is in said first position.
- [c14] 14. The grille shelter of claim 12, further comprising at least one support member connected to said roof member and at least one of said first and second side walls.
- [c15] 15. The grille shelter of claim 12, further comprising a handle attached to said roof member.
- [c16] 16. The grille shelter of claim 12, further comprising a pull cord attached to said handle.
- [c17] 17. The grille shelter of claim 12, further comprising at least one accessory item mounted to an interior surface of the grille shelter.

[c18] 18. The grille shelter of claim 12, wherein said first and second pivoting panels comprises a first section and a second section substantially perpendicular to said first section.

[c19] 19. The grille shelter of claim 18, wherein said first section and said second sections are pivotally connected.